

GIORGIO GRAESAN and Friends	DATASHEET	Code	TDS2120_00
	EUPHORIA ORO	Revision	00
		Date	12/09/2023

1. DESCRIPTION

CARRARA MARBLE grits bonded with Resins and PAILLETES, which give the product strong and eye-catching **GOLD** effect light reflections.

2. USE

EUPHORIA is suitable for decorating various types of interior wall surfaces. It is easy to apply with the KIT/NUDO stainless steel spatula.

3. SUBSTRATE PREPARATION

A correct preparation of the substrate is indispensable for the finish to show its qualities to the fullest. It is important to carry out the elimination of any poorly-anchored or powdery paint or plaster, being sure to wash or remove any mould or dust that may be present. Before applying PRIMUS NATURALE, the surface must be completely cohesive, otherwise, proceed with the application of an insulating primer, recommended especially in cases of walls in plasterboard.

In the case of application on tiles, after having removed any grease on the walls with denatured ethyl alcohol, level any large joints with localised grouting using PRIMUS AGGRAPPANTE, let it dry, then, with the KIT/I stainless steel trowel, apply a smooth and homogeneous coat of PRIMUS AGGRAPPANTE.

4. APPLICATION METHOD

EUPHORIA is ready for use.

First, colour it by pouring in the ADDITIVO COLORANTE, already stirred, in the quantity indicated in the catalogue and mixed until there is complete uniformity of the colour, making sure that none of the uncoloured product remains on the bottom or sides of the bucket.

It can be applied by hand using the KIT/NUDO stainless steel spatula. Cyclically, if necessary, go back over it to even it out and compact it, smoothing it slightly.

To prevent the detachment of residual product flakes, a coat of VETRO LUCIDO can be applied after 24 hours using a PE13 roller.

5. TOOL CLEANING

Cleaning of the tools should be performed immediately after use with water.

6. PROTECTION AND CLEANING

EUPHORIA with the addition of a coat of VETRO LUCIDO is water-repellent and absolutely washable. To clean the walls, it is advisable to use LATTE DETERGENTE (50 ml diluted in 1 litre of water).

Alternatively, it can also be protected with IPER VETRO.

7. SAFETY INDICATIONS AND HAZARD IDENTIFICATION.

The product does not require labelling in accordance with current regulations. Use the product according to current hygiene and safety regulations. After use do not disperse the containers in the environment. Allow the residues to dry well and treat them as special waste. Keep out of the reach of children. If swallowed, seek medical advice immediately and show the healthcare operator the container or label. Do not dispose of residue in sewers, waterways and soil.

For further information see the safety datasheet available on the website: www.giorgiograesan.it

GIORGIO GRAESAN and Friends	DATASHEET	Code	TDS2120_00
	EUPHORIA ORO	Revision	00
		Date	12/09/2023

TECHNICAL SPECIFICATIONS: APPLICATION	
Dilution	Ready to use
Mixing	Always mix before use
Colouring	169 colours in the catalogue (before use, eliminate any dry flakes and stir).
Tools	KIT/NUDO stainless steel spatula
Primer	PRIMUS NATURALE
Conditions of application	From +10°C to +30°C with relative humidity <85%
Number of coats	1
Curing time	24 hours at 20°C
Protective coating	VETRO LUCIDO (one coat) with PE3 brush
Washability	Complete washing with LATTE DETERGENTE if protected with VETRO LUCIDO

TECHNICAL SPECIFICATIONS: CONSUMPTION	
PRIMUS SABBIA / PRIMUS NATURALE	6 – 7 sqm/litre
EUPHORIA ORO	1 m ² /kg
VETRO LUCIDO	7 – 8 sqm/litre

COLOUR	KG 8	KG 4
T1	168ml	84ml
T2	62ml	31ml
T3	20ml	10ml
T4	7ml	3.5ml

TECHNICAL SPECIFICATIONS: PRODUCT	
Composition	Carrara marble grit, acrylic copolymer in water emulsion, additives, fillers and prismatic fragments.
Specific weight	1.25± 0.05 Kg/litre
Ph	8.0
EU limit value (Dir. 2004/42/EC) Cat. A/I: paints for decorative effects (water-based): 200 g/l	Maximum content 0.00 g/l
Storage conditions	Store in a tightly closed paint bucket, even after use and after having cleaned the sides and lid of the bucket, keep in a cool and dry place within the temperature range of + 5°C and + 30°C.
Packaging	8 – 4 kg

Giorgio Graesan & Friends guarantees that the information on this datasheet is provided to the best of its experience and technical and scientific knowledge, however it cannot assume any responsibility for the results obtained with its use as the conditions of application are beyond its control. It is advisable to always check the actual suitability of the product for the specific case. This document cancels and replaces each previous datasheet. For further technical information contact **(+39) 02.9903951** or on **Whatsapp: (+39) 3371410335**.